

# Wire - Hard & Soft Temper



Diameter		Weight		T304 Temper	
mm	SWG	kg/m	m/kg	Soft	Hard
4.811	6	0.148	6.76	0004208	
4.064	8	0.103	9.71		0004217
3.251	10	0.066	15.15	0004210	0004218
2.642	12	0.043	23.26	0004211	0004219
2.032	14	0.026	38.46	0004212	0004220
1.626	16	0.016	62.50	0004213	0004221
1.219	18	0.009	111.11	0004214	0004222
0.914	20	0.005	200.00	0004215	0004223
0.711	22	0.003	333.33	0004216	

**Finish** Drawn, bright

**Length** Ask your Wakefield Metals team about smaller/larger quantities

# Tube - Welded Seam

AS 1528



OD		Wall Thickness mm	Weight kg/m	T304	T316
mm	inch				
6.35	1/4	0.9	0.120	0003263	
7.94	5/16	0.9	0.156	0003264	
9.52	3/8	0.9	0.191	0003267	
9.52	3/8	1.2	0.257	0003265	0003320
12.70	1/2	0.9	0.261	0003270	
12.70	1/2	1.2	0.344	0003269	0003322
12.70	1/2	1.5	0.418	0003268	0003321
16.00	5/8	1.5	0.538	0003272	0003324
19.00	3/4	1.2	0.539	0003276	0003327
19.00	3/4	1.5	0.661	0003275	0003326
25.40	1	1.2	0.731	0003281	0003330
25.40	1	1.5	0.903	0003280	0003329
31.80	1-1/4	1.5	1.145	0003283	0003331
38.10	1-1/2	1.2	1.110	0003287	0003332
38.10	1-1/2	1.5	1.437	0003286	0003333
50.80	2	1.5	1.863	0003293	0003336
63.50	2-1/2	1.5	2.343	0003296	0003338
76.20	3	1.5	2.819	0003299	0003339
101.60	4	1.5	3.783	0003300	0003341
127.00	5	1.5	5.000	0019301	0019302
152.40	6	1.5	6.050	0016869	0003342

**Finish** Polished 320 Grit (400 Grit available on indent)

**Length** 6m

**10**

# Ornamental Tube

ASTM A554/1995

Not to be used in dairy, wine or other food industries



OD mm	OD inch	Wall Thickness	Weight kg/m	304	316
25.40	1	1.5	0.903	0003310	0003314
31.80	1 - 1/4	1.5	1.145		0003311
38.10	1 - 1/2	1.5	1.437	0003312	0003315
50.80	2	1.5	1.863	0003313	0003316

**Finish** 600 grit, polished

**Length** 6m

**Uses** Hand rails, furniture, etc.

# Spiral Weld Tube

Manufactured to MAF Specifications

Diameter OD & ID mm	Wall Thickness mm	Weight kg/m	Working Pressure MPa	T304L	T316L
127	2.0	6.4	2.8	0003379	0003386
152	1.5	5.9	1.9		0003389
152	2.0	7.5	2.4	0003380	0003390
203	2.0	8.0	1.7	0003382	0003391
254	2.0	12.7	1.4		0003392
254	3.0	19.1	2.1		0003393
305	2.0	15.2	1.1	0003385	0003394

**Finish** T304L and T316L fully pickled and passivated

**Length** 6m standard or up to 9m (+ 10mm, -0mm)

Spiral Weld Tube is available in both inside and outside diameters